



# Features and Benefits Performance

- 5 high efficiency gas burners
- FlameSelect® (9 power levels)
- 17K dual flame ring power burner
- OptiSim® burner
- STAR-K Sabbath compliant

#### Convenience

- Sealed burners prevent spills from entering the burner box
- Full width continuous surface enameled cast iron grates can be cleaned in dishwasher
- Push-to-turn knobs with electronic ignition
- . LED light line in the control knob for each burner

#### Design

- Stainless steel cooking surface
- Heavy-duty stainless color metal knobs for a premium look and feel
- Low-profile design for an integrated transition to the counter surface
- Perfect results are within reach with up-front centralized controls
- · Cooktop design coordinates with Bosch ovens and ventilation

## Safety

- LP conversion kit included for conversion from natural gas to liquid propane
- Residual heat indicator on every burner reminds you not to touch the grates when they are still hot
- Flame thermocouple sensing device will switch off the supply of gas if flame temporarily extinguishes


Notes: All height, width and depth dimensions are shown in inches. \*Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice.Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.


For more information on our entire line of products, go to boschappliances.com or call 1-800-944-2904.

Copyright ©2022 BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.

Litho Date: 02/2022







measurements in inches (mm)

Knob Material	Full metal
Sealed Burners	Yes
Burners with booster	
Type of grate	Cast iron
Total BTU load	41400
LP Gas Connection Rating	40100
Power of heating element (kW in boost)	
Dimension of 1st heating element (in)	
Dimension of 2nd heating element (in)	
Power of 3rd heating element (kW in boost)	
Dimension of 3rd heating element (in)	

Power of 4th heating element (kW in boost)
Dimension of 4th heating element (in)
Power of 5th heating element (kW in boost)
Dimension of 5th heating element (in)
Power of 6th heating element (kW in boost)
Dimension of 6th heating element (in)

### **Technical Specification**

**Features** 

UPC code	825225963387
Variant color	Stainless steel
Energy source	Gas
Gas type	Natural gas 15
	mbar (USA)
Alternative gas type	Liquid gas 27,5
	mbar (USA)
Watts	360
Fuse protection	15
Volts	120
Frequency	60
Approval certificates	not relevant
Power Cord Length	40"
Plug type	120V-3 prong
Required cutout size (HxWxD) (in)	3 13/16" x 28
	15/16" x 19 1/8"
Minimum distance from counter front (in)	1 7/8''
Minimum distance from rear wall (in)	3"
Overall appliance dimensions (HxWxD) (in)	+3 13/16" x 31" x 21 1/4"
Product packaging dimensions (HxWxD)	8 3/8" x 37 1/8" x 24 3/4"
Net weight	45.000
Gross weight	45.000
Total number of cooktop burners	5

Notes: All height, width and depth dimensions are shown in inches. \*Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice.Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.

For more information on our entire line of products, go to boschappliances.com or call 1-800-944-2904.

Copyright ©2022 BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.

Litho Date: 02/2022