

# Slide-In Ranges

- **Fits in Freestanding Range Cutout**  
Provides a built-in look and offers a premium replacement range option
- **Self-Cleaning Oven**  
Select from 2–4 hours depending on soil level
- **Warming Drawer**  
400 watt warming drawer for added convenience
- **Sabbath Mode**  
Temperature range 100°F – 450°F

## — Design Features —



# Slide-in Ranges

## Gas Ranges

## Dual Fuel Ranges

### 800 Series

HGI8056UC – SS  
HGI8046UC – BSS

### Benchmark®

HGIP056UC – SS

### 800 Series

HDI8056U – SS

### Benchmark®

HDIP056U – SS



- 4.8 ft<sup>3</sup> oven capacity
- Fan convection
- 9 Cooking modes
- 18K BTU center burner
- 3 Standard oven racks
- LP kit included
- 15 amp



- + QuietClose® oven door
- + 1 Telescopic rack & 2 Standard oven racks
- + 2 oven lights
- + 20K BTU dual stacked burner
- + Temperature probe



- 4.6 ft<sup>3</sup> oven capacity
- + True convection
- + 11 Cooking modes
- + Temperature probe
- 18K BTU center burner
- + 2 oven lights
- 3 Standard oven racks
- LP kit included
- 30 amp



- + QuietClose® oven door
- + 1 Telescopic rack & 2 Standard oven racks
- + 20K BTU dual stacked burner
- Temperature probe



**BOSCH**


# Slide-in Ranges

## Electric Ranges

## Induction Ranges

### 800 Series

HEI8056U – SS  
HEI8046U – BSS



- 4.6 ft<sup>3</sup> oven capacity
- True convection
- 11 Cooking modes
- 4 Elements (1 dual ring)
- 1 Warming element
- 3 Standard oven racks
- 40 amp

### Benchmark®

HEIP056U – SS



- + QuietClose® oven door
- + 1 Telescopic rack &
- 2 Standard oven racks
- + 2 oven lights
- + 4 Elements (1 triple ring)
- + 6" / 9" / 12" elements
- + Temperature probe

### 800 Series


HIH8057U – SS  
HIH8047U – BSS



- 4.6 ft<sup>3</sup> oven capacity
- True convection
- 11 Cooking modes
- + Temperature probe
- 4 Elements
- + 17 Heat levels (controls)
- + SpeedBoost®
- 3 Standard oven racks
- 40 amp

### Benchmark®

HIIP057U – SS



- + QuietClose® oven door
- + 1 Telescopic rack &
- 2 Standard oven racks
- + 2 oven lights
- Temperature probe
- + FlexInduction®
- + PowerMove®



**BOSCH**